

Available online at www.elixirpublishers.com (Elixir International Journal)

Agriculture

Elixir Agriculture 33 (2011) 2319-2322



Energy inputs and crop yield relationship for sesame production in north central Nigeria

Hussaini Yusuf İbrahim

Department of Agricultural Economics and Extension, Nasarawa State University, Keffi, PMB 135 Lafia-Shabu Campus, Nigeria.

ARTICLE INFO

Article history:

Received: 2 March 2011; Received in revised form:

24 March 2011;

Accepted: 31 March 2011;

Keywords

Energy, Sesame.

Energy efficiency, Renewable energy.

ABSTRACT

The energy-agriculture relationship is becoming very important in view of an increasing demand for food production to meet the pressure from an ever-increasing population. For these reasons, energy use pattern, energy efficiency, and energy inputs-output relationship were determined for Sesame in north central Nigeria. Data were collected from 120 farmers by using face to-face questionnaire method. The results indicated that total input energy use in sesame production was 2632.4 MJ, which was dominated by human labour energy (24.2%) and organic manure energy (21.1%). The output energy for sesame production was 13750.0MJ and the energy use efficiency ratio was 5.2. The proportion of renewable energy used (56.2%) in the surveyed Sesame farms was slightly higher than the non-renewable energy forms (44.8%), and sesame production in the study area is mainly depended on indirect energy forms. Organic manure was observed to be the most important energy input that influences the yield of Sesame in the study area.

© 2011 Elixir All rights reserved.

Introduction

The effects of agricultural activities on the environment are of growing concern. Particularly, the consumption of fossil energy, increasing energy prices, and the current debate on human influences on climate change and global warming hold a strong link to agriculture. Thus, the need for an evaluation of energy inputs use efficiency in Nigerian agriculture. This is because, efficient energy use in agriculture is one of the conditions for sustainable agricultural production, since it provides financial savings, fossil fuels preservation and air pollution reduction (Pervanchon, 2002). In Nigeria, like any other developing countries there is lack of data on energy expenditure and returns in crop production (Abubakar and Ahmed, 2010). Even though much attention is not given to the knowledge about energy expenditure in crop production in Nigeria, the energy-agriculture relationship is becoming very important in view of an increasing demand for food production to meet the pressure from an ever-increasing population. For these reasons, energy use pattern, energy efficiency, and energy inputs-output relationship were determined for Sesame in order to enhance the sustainability of it production.

Sesame (Sesamum indicum) commonly called Benniseed in Nigeria is an important oil seed crop believed to have originated from tropical Africa. The name Sesame is used in literature world wide. Sesame can be used for confectionery, biscuits, animal feeds, fertilizers, medicinal treatment and as solvents. The spectrum of uses Benniseed had been put into is not unconnected with its unique nutritional and chemical composition. In Nigeria some small/medium level commercial ventures are now predominantly Benniseed-based (Raw Materials Research and Development Council, 2004). For instance, in some rural communities in Nasarawa state, soap is prepared from Benniseed and its by-product, by women. It is

also useful in the preparation of locally brewed beverages "Kunu Ridi", Snacks "Kantu ridi" and Kulikuli" the cake obtained after extracting oil from the seed or used to prepare a local soup known as "Miyar Taushe". Sesame is produced in all the 13 Local Government Areas of Nasarawa state, but the major producing LGAs include Doma, Awe, Obi, Keana, Nasarawa and Lafia. Sesame production in Nasarawa state has increased substantially in the last five years. The average annual output in the state is about 40,000 MT ha⁻¹ (Rahman *et al.*, 2007).

Materials and methods

Nasarawa state is located in the middle belt zone of the country. It lies between latitude 70 and 90 North and longitudes 7^o and 10^o East, and shares common boundaries with Benue state to the South, Kogi state to the West, the Federal Capital Territory (FCT), Abuja, Kaduna and Plateau State to the North-East and Taraba State to the South-East. The mean temperature range from 25°C in October to about 36°C in March, while rainfall varies from 131.73 mm in some places to 145 mm in others. Alluvial soils are found along the Benue Trough and their flood plain. These are always swampy in nature due to availability of water all the year round. The forest soils, which are rich in humus, are found in most parts of the state. There are also sandy soils in some parts of the state. The three major Sesame producing L.G.As in the state (Doma, Awe and Obi) were purposively sampled and simple random sampling technique was used to select 40 farmers from each LGA. A total of 120 farmers were used for the study. An interview schedule was used to obtain information on production inputs as well as outputs.

The amounts of inputs were calculated on per hectare basis and these input data were converted into energy equivalent by multiplying with the coefficient of energy equivalent (Kizilaslan, 2009). For determination of energy equivalent

Tele:

E-mail addresses: hussein464@yahoo.com

coefficients, previous studies were utilized. These sources are given in Table 1. The energy equivalences of unit inputs were expressed in Mega Joule (MJ) terms. Total input equivalent can be calculated by summing of energy equivalences of all inputs in MJ terms. Data analysis was done using descriptive statistics and energy use efficiency was estimated as follows:

Energy Efficiency = Energy Output (MJ ha⁻¹)
Energy Inputs (MJ ha⁻¹)

The energy inputs-output relationship was estimated using production function analysis. Three functional forms (Linear, Semi-log and Cobb-Douglas) were fitted to the data and the lead model was selected base on the number of significant variable, the R² value and the signs of the coefficients. The implicit form of the model is specified as follows;

2

$$Y=f(X_1, X_2, X_3, X_4, X_5, X_6, X_7, U)$$

Y= Sesame yield (kg ha-1)

 X_1 = Sesame seed energy (MJ)

 X_2 = Machinery energy (MJ)

X₃= Pesticides energy (MJ)

X₄= Organic manure energy (MJ)

 X_5 = Diesel energy (MJ)

 X_6 = Human labour energy (MJ)

 $X_7 = NPK$ fertilizer energy (MJ)

U= error term

The elasticity value for each of the energy inputs was computed using the expression

$$\dot{\epsilon}_i = MPP_i/APP_i \dots$$

where, $\acute{e}_{i}=$ elasticity value for the ith energy input, $MPP_{i}=$ marginal physical product for the ith energy input, and $APP_{i}=$ average physical product with respect to the ith energy input. In the linear production function, the coefficients represent the MPP. However, $APP=Y/X_{i}$, hence, equation 3 can be re-written as $\acute{e}_{i}=MPP/Y/X_{i}$, which becomes $MPP*X_{i}/Y$. X_{i} and Y are the means for the ith energy input and the yield of Sesame respectively. Table 1 was used to convert the inputs and output into their energy equivalents respectively.

The NPK 15:15:15 brand of compound fertilizer is widely used in the study area. The fertilizer blend contains Nitrogen, Phosphorus and Potassium combined in a ratio of 15:15:15 packaged in a 50kg bag. This implies that a 50kg bag of NPK 15:15:15 fertilizer contains 7.5kg of each of the elements N, P and K. According to Singh *et al* (2002), the energy equivalent of a unit (kg) of elemental N, P and K are 60.60MJ, 11.10MJ and 6.70MJ respectively. Hence, the total energy equivalent of NPK 15:15:15 in a 50 kg bag was 588MJ.This is equivalent to 11.76MJ per kg of the fertilizer.

Results and Discussion

Energy use pattern in Sesame production

The inputs used in Sesame production and their energy equivalents, output energy equivalent, energy ratio and energy productivity are presented in Table 2. About 1.7litres of pesticide, 45kg of NPK fertilizer were used in Sesame production on a hectare basis. The use of diesel and machine hours was 7.5 litres and 1.6 hours respectively. Furthermore, about 1850kg of organic manure and 325 man hours of labour were used per hectare. The total energy equivalent of inputs was calculated as 2632.49MJ per ha. Human labour energy had the highest share, of 24.2%. This is obviously due to the prevailing practice in the study area where all management practices for Sesame production are done using human labour energy except land preparation which is mostly done with tractors. Organic manure energy and Diesel energy had (21.1%), and (19.1%)

respectively. Pesticides contributed the least amount of energy (0.64%). The average yield of sesame was about 550kg ha-1 and its energy equivalent was calculated to be 13750.0MJ. Based on these values, the energy efficiency for the production of Sesame was 5.2. The value obtained for energy efficiency was quite higher compared to that obtained for Millet (2.4) in Nigeria by Abubakar and Ahmad (2010). The higher energy efficiency value indicated that a higher yield per hectare was obtained in the study area and the Sesame farmers are quite efficient in terms of energy use. This finding is a likely reason why Nasarawa state is noted as a major Sesame producing state in Nigeria.

Energy forms for Sesame production

Direct, indirect, renewable and non-renewable energy forms used in Sesame production were also investigated (Table 3). The results show that the share of direct input energy was 43.3% in the total energy input compared to 56.7% for the indirect energy. This result shows that sesame production in the study area is mainly depended on indirect energy form dominated by organic manure. A similar finding was also made by Akpinar, et al (2009) in Turkey. On the other hand, non-renewable and renewable energy forms contributed 44.8% and 56.2% of the total energy input respectively. This result shows that the proportion of renewable energy used in the surveyed Sesame farms was slightly higher than the non-renewable energy forms. This implies that Sesame production in the study area does not depend heavily on fossil fuels which in the long run, may lead to environmental problems such as land and water pollution. The renewable sources represent an effective alternative to fossil fuels for preventing resources depletion and for reducing air pollution (Cosmi, 2003).

Relationship between energy inputs and Sesame yield

The linear model gave the best fit to the data and was selected for further analysis. The result shows that most of the variables were consistent with priori expectations. A linear relationship between energy inputs and yield was also observed by Abubakar and Ahmad (2010. The result as presented in Table 4 shows that about 88% of the variation in Sesame yield is a result of the energy inputs included in the model. This result implies that Sesame yield is dependent on energy inputs. The coefficient for the energy inputs for seed was significant (P<0.01), while those of the energy inputs for machinery energy and organic manure were significant at (P<0.05) and (P<0.10) respectively. However, the following energy inputs; human energy, fertilizer, pesticide and diesel had negative signs for their coefficients and were not significant at (P=0.10).

Elasticity estimates for energy inputs

Elasticity estimates are particularly useful for determining the relationship between energy inputs and yield (Hartili *et al.*, 2006). Among the energy inputs in the linear production function model, manure energy was observed to be the most important energy input that influences the yield of Sesame in the study area (Table 5). This was closely followed by human labour energy. A 1 % increase in manure and human labour energy will lead to about 1.3% and 1.2% increase in the yield of Sesame respectively. Diesel on the other hand was the energy input that least influences the yield of Sesame.

Conclusion

The efficiency of energy use in Sesame production was very high, and renewable energy sources especially organic manure and human labour are very essential for the sustainability of Sesame production in the study area.

References

- 1. Abubakar M.S. and D. Ahmed (2010). Pattern of Energy Consumption in Millet Production for Selected Farms in Jigawa, Nigeria. *Australian Journal of Basic and Applied Sciences*. 4(4): 665-672.
- 2. Akpinar, M.G., O. Burhan., C.Sayin and C. Fert (2009). An Input-Output Energy Analysis on Main and Double Cropping Sesame Production. *Journal of Food, Agriculture and Environment*.7(3 and 4): 464-467.
- 3. Cosmi, C., Macchiato, M., Mangiamele, L., Marmo, G., Pietrapertosa, F. and Salvia, M. (2003). Environmental and economic effects of renewable energy sources use on a local case study. *Energy Policy* 31(5):443-457.
- 4. Erdal G., G. Kemal., K. Esengun, H. Erdal and O. Gunduz (2007). Energy Use and Economical Analysis of Sugar Beet Production in Tokat Province Turkey. *Energy* 32:35-41
- 5. Hatirli S. A., B. Ozkan and C. Fert (2006). Energy Inputs and Crop Yield Relationships in Greenhouse Tomato Production. *Renewable Energy*. 31:427-438.
- 6. Kızılaslan, N. (2009) Energy use and input-output energy analysis for apple production in Turkey Journal of Food, Agriculture & Environment. 7 (2):419-423.
- 7. Pervanchon, F., Bockstaller, C. and P. Girardin, P. (2002). Assessment of energy use in arable farming systems by means

- of an agro-ecological indicator: the energy indicator Agricultural Systems 72:149–172.
- 8. Pimentel, D., (1992). Energy Inputs in Production Agriculture. Energy in Farm Production, Elsevier, and Amsterdam. pp; 13-29
- 9. Rahman, S.A., S. Mohammed and M. Ebayaya (2007) Sesame production, processing and Marketing in Nasarawa state of Nigeria. A report of consultants submitted to GTZ Lafia
- 10. Raw materials Research and Development Council (2004). *Report on Survey of Agro-Raw materials in Nigeria: Beniseed.* Publisher Raw materials Research and Deve lopment council Garki-Abuja. 1st Edt. Pp. 1-87
- 11. Singh, H., Mishra, D. and Nahar, N.M. (2002). Energy use pattern in production agriculture of a typical village in Arid Zone India-Part I. Energy Conversion and Management 43(16):2275-2286
- 12. Singh, S., S.R. Verma and J.P. Mittal, 1997. Energy requirements for production of major crops in India. Agricultural mechanization in Asia, Africa and Latin America, 28(4): 13-17.
- 13. Singh, J.M. (2002). On Farm Energy Use Pattern in Different Cropping Systems in Haryana, India. MSc. thesis, International Institute of Management University of Flensburg, Germany.

Table 1: Energy equivalent of inputs and output in agricultural production

Variables	Unit	Energy Eq (MJ/ unit)		
Human labour	(Man hr)	01.96	(Erdal, et al., 2007)	
Machinery	(h)	62.70	(Erdal, et al., 2007)	
Pesticides	(lt)	10.00	(Singh et al., 1997)	
Manure	(kg)	0.30	(Hatirli, 2006)	
Diesel oil	(lt)	47.8	(Pimentel 1992)	
Sesame seed	(kg)	15.2	(Akpinar, et al., 2009)	
NPK Fertilizer	((kg)	11.76*		
Sesame yield	(kg)	25.0	(Singh 2002)	

^{*}Explanation on the source of 11.76 MJ per Kg of NPK Fertilizer is given below.

Table 2 Energy consumption pattern for Sesame production

Inputs (Units)	Quantity/ha	Energy equivalents	%
		(MJ)	
labour (Man hr)	325.0	637.0	24.2
Machinery (h)	1.6	103.5	3.9
Pesticides (1t)	1.7	17.0	0.64
Manure (kg)	1850.0	555.0	21.1
Diesel oil (It)	7.5	501.9	19.1
Sesame seed (kg)	19.0	288.8	10.97
NPK Fertilizer (kg)	45.0	529.2	20.1
Total energy input (MI)		2632.4	100.0
Sesame yield (kg)	550.0	13750.0	
Energy efficiency		5.2	

Table 3 Energy forms for Sesame production

Energy forms	Quantity/ha	0/0
	(MJ)	
Direct ^D	1515.8	43.3
Indirect ^I	891.1	56.7
Total energy input	2406.9	100.0
Renewable ^R	1480.8	56.2
Non-renewable ^N	1151.6	44.8
Total energy input	2632.4	100.0

Table 4 Regression output for the linear production function

Energy inputs	Coefficients	Standard Error	t-value
Constant	4132.1	4267.8	0.97
Sesame seed	24.2	2.50	9.60*
Machinery	304.6	122.9	2.5**
Pesticides	-130.1	151.3	-0.14
Manure	0.38	0.19	2.01****
labour	2.0	1.9	1.1
Diesel oil	-206.8	183.7	-1.1
NPK Fertilizer	2.8E-02	1.5	0.9
\mathbb{R}^2	0.88		

^{*}significant at 1%** significant at 5% and ***significant at 10%.

Table 5 Elasticity estimates for energy inputs in Sesame production

Energy inputs	Elasticity values	
Sesame seed	0.82	
Machinery	0.88	
Pesticides	-0.40	
Manure	1.27	
labour	1.18	
Diesel	-2.82	
NPK fertilizer	1.0E-03	

^B: human and diesel, ^I: include machinery, manure, pesticides, NPK fertilizer and seed

R: include human, manure and seed, ^N: include machinery, pesticides, NPK fertilizer and diesel